



# QC4-BH and QC7I-MH Water Filters for Coffee Makers

9272-00 • 9272-41 • 9613-01

**Premium quality water that results in better tasting hot beverages and reduced machine maintenance**

## BENEFITS

- Removes chlorine and other off-tastes and odors
- Exclusive Precoat technology filters out dirt down to 1/2 micron in size
- Self-contained scale inhibitor feed inhibits costly mineral scale build-up
- Increases energy efficiency
- Increases holding time
- Increases brewer life – reduces corrosion
- NSF Standards 42 and 53 listed

### QC4-BH APPLICATION/SIZING

For smaller plumbed in coffee brewers with a flow rate of .5 gpm or less.  
3,000 gallon capacity

### QC7I-MH APPLICATION/SIZING

For urns and larger plumbed in brewers with flow rates above .5 gpm.  
9,000 gallon capacity



QC4-BH Filter: 9272-00  
BH Replacement  
Cartridge: 9612-00

QC7I-MH Head: 9272-41  
MH Cartridge: 9613-01  
Note: Head and Cartridge  
sold separately

## INSTALLATION TIPS

- Never use saddle valve for connection
- QC4-BH: Use minimum 1/4" water line
- QC7I-MH: Use minimum 3/8" water line
- **Flush cartridge by running two gallons through machine at full flow**

## OPERATION TIPS

- Change cartridges:
  - on a regular 6 month preventative maintenance basis
  - when the pressure gauge indicates a pressure less than 10 psi *when the system is operating*
  - or at least annually

**Always flush the filter cartridges when changing**



## SPECIFICATIONS

Dimensions: 16"H x 5"W x 5"D

Inlet connection: 1/4"

Service flow rate: Minimum .1 gpm  
Maximum .5 gpm

Pressure: Minimum 10 psi  
Maximum 125 psi (non-shock)

Maximum temperature: 100°F (38°C)

No electrical connection required

Shipping weight: 4 lbs.

Operating weight: 9 lbs.

## LIMITED WARRANTY OF PHYSICAL QUALITY

If, within eighteen months after manufacture or twelve months after purchase (whichever occurs first), any part of Everpure, Inc. manufacture which is returned to its factory, shipping charges prepaid, is found to be defective in material or workmanship in the judgement of Everpure's engineers, Everpure, Inc. will repair or replace such part at no charge, f.o.b., Westmont factory. Everpure, Inc. however, shall not be liable for damages or delays caused by any defective material or workmanship, or by failure of any parts due to normal wear and tear. Everpure, Inc. will not be responsible for products which malfunction due to user neglect or unauthorized modification.

NOTE: Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. Similarly, some states do not allow the exclusion or limitation of consequential or incidental damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights which may vary from state to state.



## SPECIFICATIONS

Dimensions: 29"H x 5-1/2"W x 5"D  
("H" dimension includes 2-1/2"  
clearance for cartridge changing)

Minimum inlet connection: 3/8" OD  
Service flow rate: Minimum .5 gpm  
Maximum 1.67 gpm

Pressure: Minimum 10 psi  
Maximum 125 psi (non-shock)

Maximum temperature: 100°F (38°C)

No electrical connection required

Shipping weight: 8 lbs.

Operating weight: 14 lbs.



NSF's Certification Program is accredited by the American National Standards Institute

NSF's Certification Program is accredited by the Deutscher Council for Accreditation

System Tested and Certified by NSF International against ANS/NSF Standard 42 and 53 for the reduction of:

Standard No. 42: Aesthetic Effects  
Chemical Unit  
Taste and Odor Reduction  
Chlorine Reduction, Class I  
Mechanical Filtration Unit  
Particulate Reduction, Class I:  
99.9+% reduction of particles  
one-half micron and larger in size  
Standard No. 53: Health Effects  
Mechanical Filtration Unit  
Turbidity Reduction  
Cyst Reduction  
Asbestos Reduction

Check for compliance with state and local laws and regulations. Do not use where the water is microbiologically unsafe, or with waters of unknown quality without adequate disinfection before or after the unit. May be used with disinfected water where filterable cysts may be present.

**EVERPURE**  
WATER YOU CAN TRUST®